

# DuraVision™ Mirror

## Quarter Dome



### Fabrication & Material

**Mirror:** 1/8" (0.3 cm) polycarbonate with a pure silver reflective coating on inside surface and a tensile strength of 9,400 psi. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 90° view.

**Frame:** 3/16" x 1" (0.5 x 2.5 cm) steel has recessed holes for fastening and slotted flange for mirror. Powder coated to provide durable smooth finish.

### Warranty

3 year limited replacement warranty.

### Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

### Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Model	MQD-N18
Weight	9.5 lbs / 4.3 kg

Dimensions	in	cm
Length	27"	68.6
Height	9"	22.9
Depth	19"	48.3

### Finishes

- Mirror:** Silver
- Frame:** Almond

### Options

- 12" (30.5 cm) Mirror

### Assembly

Fit mirror and foam backing to frame.  
Attach to ceiling or wall.

*\*Intended for indoor use only*

