

Wink™

Lounge Arm Chair



Model	WC10
Weight	42 lbs / 19.1 kg

Dimensions	in	cm
Seat Height	18.5"	47
Seat Width	22"	55.9
Overall Height	31.4"	79.8
Depth	18.7"	47.5
Overall Width	26"	66
Arm Height	25.4"	64.5
Upholstery	yd	m
COM Total	2.4	2.2
COM Seat	1	0.9
COM Back	1.4	1.3

*View our upholstery selection on our website.
Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- Ganging kit
- Bolt-down kit
- Replacement cushions
- TB133 Upholstery Upgrade
- Factory Ballasting (50 lbs / 22.7 kg)

*Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required.

*Intended for indoor use only

Fabrication & Material

Frame: One-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading) is chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Molded-in access port with threaded screw cap for ballast weighting capability. Non-removable steel encased nylon glides for floor protection.

Back: 5" (12.7 cm) polyurethane foam is fully upholstered and stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection.

Seat: Upholstered 4" (10.2 cm) polyurethane foam with a 6" (15.2 cm) bullnose glued to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. The seat features both a side and back clean-out for easy cleaning. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Frame: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexicide® or Oxivir Five 16®) per manufacturers' instructions.

Upholstery: Refer to upholstery manufacturer's cleaning instructions.

Performance Test Standards

- Tested to 750 lb (340.2 kg) static load
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

