



Model	FEN40
Weight	18 lbs / 8.2 kg

Dimensions	in	cm
Overall Height	18.1"	45
Overall Depth	20"	50.5
Overall Width	24"	60.7

Finishes

See Design Guide for finish options.

Options

- Bolt-Down Kit
- Factory Ballasting (50 lbs / 22.7 kg)

**Ballastable up to 100 pounds (43.5 kg) of dry sand. On site ballast materials not supplied by Norix.*

Assembly

None required

Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Ligature resistant design with no internal openings. Molded-in floor glides protect the floor from scratching without risking the safety of residents and staff. Molded-in access port with threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

Lifetime warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)
- Tested to 750 lb (340.2 kg) static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

